# FlexSmart<sup>®</sup> Series Credentials MIFARE<sup>®</sup> Cards • 1430, 1436, 1440, 1446

High Security - Mutual authentication, data encryption and unique 32-bit serial number.

Read/Write Functionality - Ideal for e-Purse functions.

True Credit Card Thickness - Use with all direct image and thermal transfer printers.



## ACCESS interoperability.

HID's FlexSmart MIFARE offerings encompass the industry's broadest range of open standard contactless smart card products. HID MIFARE is a credit card-sized credential ideal for diverse applications such as access control, cashless vending, public transportation, corporate and campus applications, event ticketing, customer loyalty and photo ID cards.

Manufactured to the highest quality standards, HID MIFARE credentials have the memory structure and capacity to store multiple applications on a single credential. Securely separated sectors, each protected by a set of two keys and programmable access conditions, allow complex applications and provide for future expansion. The data on the card is protected with encryption keys used in the mutual authentication process. Therefore, no important data will be shared until the card and reader have been authenticated to each other.

When security and performance count most, HID's FlexSmart MIFARE cards can be produced with visual security and anti-counterfeiting features such as holograms, ultra-violet fluorescent inks, micro-printing or a custom logo to quickly and easily identify genuine cards.

### **Key Features**

- Proven, Reliable Technology Offers extremely consistent read range. Use is unaffected by body shielding or variable environmental conditions, even when close to keys and coins.
- Fast Processing and Data Communication Transaction times are less than 100 milliseconds for a typical secure ticketing transaction.
- Multiple Memory Types Available in MIFARE IK and 4K.

# Features

Long Life	Passive, no-battery design allows for an infinite number of	Many Ordering Options
Durability	reads.	Including magnetic stripe, external card numbering, vertical slot punch, custom artwork, and contact smart chip module.
,	Strong, flexible and resistant to damage.	Memory Specification
Photo ID Compatible	Print directly to the card with a direct image or thermal transfer printer. Slot punch vertically for easy use.	IK Byte (8,192 bits) or 4K Bytes (32,768 bits) Memory Sector 0 is used as the MIFARE® Application Directory (MAD)
<b>PVC Card Surface</b>	Card is optimized for dye sublimation printing.	<ul> <li>Unique 4 Byte (32 bit) ID per card (CSN)</li> <li>Each sector uses two encryption keys</li> </ul>
Customizable	Specify your own text or graphics artwork.	- Key "A" to read only - Key "B" to read/write
Thin	0.030" (0.076 cm) card can be carried with credit cards in a wallet or purse. Use with a strap and clip as a photo ID badge.	• Each encryption key is 6 Bytes (48 bits)
Dimensions	2.125" x 3.375" x .03" (5.4 x 8.57 x 0.076 cm)	
Weight	0.20 oz. ( 6 g )	
Typical Maximum Read Range*	Up to 4" (10 cm)	
Operating Temperature	Model 1430, 1440 PVC Cards: -40 to 122°F (-40 to 50°C) Model 1436, 1446 Composite Cards: -40 to 158°F (-40 to 70°C)	
<b>Operating Humidity</b>	5%-95% Non-condensing	
<b>Operating Frequency</b>	13.56 MHz	
<b>RF</b> Interface	ISO 14443 A, Parts 1-3	
<b>Transaction Time</b>	< 100 ms	
Baud Rate	106 kbps	
Memory Type	EEPROM, IKbyte (8,192 bits) or 4 Kbytes (32,768 bits)	
Multi-Application Memory	MIFARE 1K: memory arranged in 16 64-byte Sectors MIFARE 4K: memory arranged in 40 Sectors: 32 sectors of 64 bytes, 8 sectors of 256 bytes	
Write Endurance	100,000 cycles min.	
Data Retention	10 years min.	
Material and Finish	Gloss white/white PVC or PVC/Polyester Composite	
Card Marking	Inkjet Standard, Laser Engraving optional	
Custom Graphics	Optional	
Slot Punch	Vertical slot punch optional	
Programming	Factory or Field Programmable	
Part Number	Model 1430 PVC MIFARE IK Card Model 1440 PVC MIFARE 4K Card Model 1436 Composite PET/PVC MIFARE IK Card Model 1446 Composite PET/PVC MIFARE 4K Card	
Description	MIFARE Card, ISO Thick, Photo Imageable	
Warranty	Lifetime - see Sales Po	licy for complete details
		*Dependent on local installation conditions.

© 2007 HID Global Corporation. All rights reserved. HID, the HID logo, and FlexSmart are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. I/2007



# **ACCESS** experience.

#### HID Global Offices:

Corporate North America 9292 Jeronimo Road Irvine, CA 92618-1905 U.S.A. Phone: (800) 237-7769

Phone: (800) 237-7769 Phone: (949) 598-1600 Fax: (949) 598-1690 Asia Pacific 19/F 625 King's Road North Point Island East Hong Kong Phone: +852 3160-9800 Fax: +852 3160-4809 Latin America Circunvalacion Ote. #201 B Despacho 2 Col. Jardines del Moral Leon 37160, Gto. Mexico Phone: +52 477 779 1492 Fax: +52 477 779 1493

For best results, please print on recycled paper.

Europe, Middle East & Africa Homefield Road Haverhill, Suffolk CB9 8QP England Phone: +44 (0) 1440 714 850 Fax: +44 (0) 1440 714 840

MKT-MIFARE-CARD-DS-EN

hidcorp.com

#### ASSA ABLOY