Back Packaging



Seos Key Fob - 526

Portable Credential for Key Ring Applications.

Designed for HID Signo and single technology iCLASS SE and iCLASS SE Express Readers.

- · This product is not compatible with the multiCLASS SE reader family.
- · Please ensure that this page is completed and submitted alongside your first order to activate part numbers.
- · Allow 1-2 days for part activation.
- · See datasheet for compatibility and performance details.
- ☐ I have read the datasheet and understand that this product is not compatible with the multiCLASS SE reader family.

Name	
Company	

Ensure each required option has been checked with the appropriate choice to fulfill a completed order form.

Base Model **⊠** 526

Memory Size

✓ 6-8K Bytes

Secure Identity Object Programming (select one option)

- P Programmed with Secure Identity Object (SIO)

Front Packaging

🛛 N - Black ABS body, grey TPE insert with HID logo

Back Packaging

N - Seos logo and marking panel

Key Numbering¹

- N No external ID number
- A Sequential Matching Encoded/Printed (Engraved)
- **B** Sequential Encoded/Sequential Non-Matching Printed (Engraved)
- C Random Encoded/Non-Matching Sequential Printed (Engraved)

Enter your final options from the above selections. Example: 5266PNNA

Final Part Number 5266 N N

1.56" (39.5 mm)

Seos Programming Information

Format Number	Field Name(s) e.g. Facility Code	Value
HID Elite ICE number		

Front Packaging

HID

1.25" (31.75 mm)

Encoded Start Number	Encoded Stop Number
Printed Start Number	Printed Stop Number

Y = Seos Programming

12345 = Card ID Number

YYYYYYYY = Sales Order Number

November 2022 PLT-02630, Rev D.3 71

¹ The ID number is marked on the back of the key fob, all options include a printed sales order number

² Available with 7 byte static UID for ISO14443A UID migration and interoperability. This feature reduces privacy and is not recommended. Contact your local sales or pre-sales representative for more informaiton