

Seos Clamshell - 565

Highly Durable Slot Punched Contactless Smart Card.

Ensure each required option has been checked with the appropriate choice to fulfill a completed order form.

Base Model ☒ **565**

Memory Size

☒ **6- 8K Bytes**

Secure Identity Object Programming (select one option)

- ☐ **P** - Programmed with Secure Identity Object (SIO)
☐ **V** - Unprogrammed, for use with iCLASS SE Encoder

Front Packaging

- ☐ **M** - Plain White Matte Vinyl with Seos logo
☐ **C** - Custom Artwork – Specify Custom Artwork Number¹

Back Packaging

- ☐ **S** - ABS Base with Molded HID Logo
☐ **C** - Custom Artwork – Specify Custom Artwork Number¹

Key Numbering²

- ☐ **N** - No external ID number
☐ **A** - Sequential Matching Encoded/Printed (Engraved)
☐ **B** - Sequential Encoded/Sequential Non-Matching Printed (Engraved)
☐ **C** - Random Encoded/Non-Matching Sequential Printed (Engraved)

Slot Punch

☒ **V** - Vertical Slot Punch

Enter your final options from the above selections. Example: 5656PMSAV

Final Part Number	5656					V
-------------------	------	--	--	--	--	---

Seos Programming Information

Format Number	Field Name(s) e.g. Facility Code	Value	QTY	Encoded Start Number	Encoded Stop Number
HID Elite ICE number				Printed Start Number	Printed Stop Number

¹ For new artwork files, contact Customer Service for custom artwork number, lead-times, and cost

² The ID number is marked on the back of the clamshell, all options include a printed sales order number

Available with 7 byte static UID for ISO14443A UID migration and interoperability. This feature reduces privacy and is not recommended. Contact your local sales or pre-sales representative for more information.

