

# 125 KHz PROXIMITY ORDER GUIDE



All credential orders must have the following information:

- Credential Part Number
- Bit Format Code
- Facility Code (if required by format)
- Starting Card Number
- Any special instructions

### Credential Types

- 3326 Clamshell
- 3336 PVC ISO Mag
- 3391 PVC Disc
- 3386 PVC ISO
- 3536 Composite ISO Mag
- 3586 Composite ISO
- 3546 Keyfob

### Options / Special Instructions

#### **Programming**

- Programmed
- Initialized Only

#### **Card Numbering**

- Matching Internal & External Numbering
- No External Numbering
- Sequential Internal / Non-Matching External Numbering

#### **Slot Punch**

- Vertical Slot Punch
- Horizontal Slot Punch

#### **Custom Artwork**

Contact us at [sales@3millid.com](mailto:sales@3millid.com) for a quote, lead time and proof.

## 125 kHz PROXIMITY CREDENTIAL FORMAT SPECIFICATIONS

Format Code	OEM	3milliD Format Code	Facility Code Range	Possible Card Range
H10301	HID	26A	0-255	0-65,535
40134	Indala	26I	0-255	0-65,535
AWID26	AWID	26W	0-255	0-65,535
BSB	HID	27B	0-8191	0-16,383
Quadrakey	Honeywell	32Q	None	0-4,294,967,295
Codepoint	HID	33C	0-16,383	0-65,535
DSX	DSX	33X	0-127 (Standard 17)	0-16,777,215
L10001	Geoffrey	34G	0-4,095	0-1,048,575
N10002	Northern Computer	34N	0-65,535	0-65,535
H5XXXX	HID C1000	35C	0-4,095	0-1,048,575
C10202	Continental	36C	0-65,535	0-65,535
C15001	KeyScan	36K	0-255	0-65,535
S12906	Simplex	36S	0-255 (Standard 217)	0-16,777,215
H10302	HID	37A	None	0-34,359,738,367
H10304	HID	37B	0-65,535	0-524,288
S10401	AMAG	37M	0-63 (Standard 9)	0-535,870,911
C10106	GE CASI	40G	151,552 - 151,632	0-457,681
Amano40	Amano	40M	None	0-1,099,511,627,775
Initialized	HID	42Z	None	initialized
8 Digit Clock & Data	HID	8CD	None	0-99,999,999

Please call or email 3milliD Corporation with other format inquires.

9249 S. Broadway  
 Building #200 Suite 826  
 Highlands Ranch, CO 80129

Office +1 303 475 4972  
 Fax +1 866 382 6701  
 support@3millid.com