bioCLASS RKLB57, RWKLB575 and BIO500

Smart Card Reader/Field Enroller or Reader/Writer with Biometric Verification • 6180, 6181, 6188, 6190

- Increased Security Multi-factor authentication with smart card reader, keypad and fingerprint verification module
- Reader and Field Enroller One unit (field enroller) provides access control verification and fingerprint template enrollment
- Added Privacy Fingerprint templates are stored on the iCLASS[®] smart card to alleviate privacy and database management concerns
- Compatibility Works with the broadest range of open standard contactless smart card products, available from over 40,000 resellers worldwide

ACCESS interoperability.

Using 13.56 MHz contactless smart card technology, the bioCLASS[™] RKLB57 and RWKLB575 family of readers provides users with new options for supporting multi-factor authentication of identity. Combining contactless card presentation with a fingerprint biometric, the bioCLASS reader can also be used with personal identification numbers (PIN).

Featuring multi-factor authentication, HID's bioCLASS readers offer the highest level of security. Storing the fingerprint template only on the smart card, users benefit from the increased security, faster throughput, easier system management, lower costs for the biometric reader and reduced concerns over individual privacy. Choose from three levels of security, including card/biometric fingerprint, card/PIN and card/fingerprint/PIN.*

The bioCLASS RKLB57 is a read-only, contactless smart card reader with a keypad and biometric sensor that provides access control verification and fingerprint enrollment all in one reader.

- Field Enroller (6180BxR) can be configured as a dual-purpose reader/enroller, singlepurpose enroller-only or reader-only
- ▶ Field Enroller (6180BxR) provides additional field configuration options allowing for selection of language (choose from 9 languages), administration rights (store rights on card or in reader) and template storage location (small templates fit anywhere on iCLASS[®] cards)
- Field Enroller comes with multilingual quick start guide and English instructional CD.
- Site unique keys protect card access control data (Elite) or biometric templates (Bio-Elite).

The bioCLASS RWKLB575 is a contactless smart card reader/writer with keypad and biometric sensor that provides access control verification, in addition to host-controlled read/write to iCLASS smart cards.

* Security level configuration is not dynamic. Field or factory configurable using configuration card.

Features

Specifications

Security 64-bit authentication keys are extremely secure. Readers Indoor Design Rugged, weatherized polycarbonate enclosure provides reliable and cards require matching keys to function. All RF data transmission between the card and keypad reader is performance and resistance to vandalism. (Please note that these encrypted, using a secure algorithm. The key management products are not suitable for outdoor use.) system reduces the risk of compromised or duplicated cards. Enrollment Use one of two methods for fingerprint template (and PIN enrollment if desired) onto iCLASS® smart cards. (1) Field **Graphical Display** The backlit graphical LCD display offers a 60 x 18 mm viewing area, 120 x 32 resolution. It is factory preset to provide written instructions to the user. Fully customizable, Enroller (6180BxR) allows for dynamic configuration of reader the display also describes the function of the user function type (reader/enroller, enroller-only or reader-only). Enrollerenabled reader types allows for enrollment of fingerprint templates (and PINs) onto iCLASS smart cards. (2) CP575A keys. Multilingual version available in Field Enroller (6180BxR) unit. iCLASS Card Programmer is PC software that enables field Keypad Offers 12 discrete switches with metal keycaps. Raised tactile programming of access card numbers, plus enrollment of mark on the fifth key for visually impaired users. Configurable fingerprint templates and PINs onto iCLASS smart cards. audio feedback. Backlit numbers in bezel overlay, above each key. Lighting is configurable: Always On, Triggered by Card Read, or Triggered by Key Press. RKLB57 / RWKLB575 Field Enroller (Reader/Enroller)*** 6180BxR (Wiegand) **Reader ****** 6180BxT (Wiegand) 6188BxT (Clock-and-Data) Model Numbers Reader / Writer ***** Reader / Writer 6181BxT (Wiegand and RS232) 6181Bx4 (Wiegand and Full-Duplex RS485) 6181BxU (Wiegand and USB) 6181BxB (Wiegand and UART) iCLASS Card: Up to 4" (10.2 cm) iCLASS Key/Tag: Up to 1.25" (3.2 cm) Read Range Mounting plate attaches to US/EU/ Asian back box, 52-60 mm screw hole spacing (vertical or horizontal). LCD/Keypad reader housing latches onto mounting plate; fingerprint module secured to reader with a screw. Mounting 8.43" x 4.17" x 2.28" (21.4 x 10.6 x 5.8 cm) Dimensions Weight 13.5 oz. (382 g.) **Power Supply** 9-12 VDC, Linear supply recommended * Current Requirements 245 mA AVG, 299 mA PEAK 32° F to 113° F (0° C to 45° C) **Operating Temperature Operating Humidity** 5% to 95% relative humidity non-condensing Environmental Indoor Only **Protection Class** none Transmit Frequency 13.56 MHz Cable Distance Wiegand/Clock-and-Data Interface: 500 ft (150 m) (22AWG), RS232: 50 ft (15 m), RS485: 4000 ft (1220 m), USB: 16 ft (4 m), UART: 1 ft (0.30 m) iCLASS 15693 & 14443B - read-only on 16k bit (2k Byte), 32k bit (4k Byte); HID Application iCLASS 15693 & 14443B - read/write (RWKLB575 only) on 16k bit (2k Byte), 32k bit (4k Byte); Application Space **Card Compatibility** Field Enroller - English, International Spanish, Brazilian Portugese, German, Italian, French, Russian, Chinese (Mandarin), Korean, Japanese Reader - English, International Spanish, Brazilian Portugese, German, French, Chinese (Mandarin) Language Support** UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS Certifications UL94 Polycarbonate **Housing Material** Optical **Fingerprint sensor type** Resolution 500 dpi, 256-bit gray scale, 18 x 22 mm sensor area Card read < 0.5 sec Fingerprint capture < 2 sec, typical I sec Verification of captured finger < I sec Timing False Accept/Reject Rate FAR < 0.01%, FRR < 0.01% Warranty Warrantied against defects in materials and workmanship for one year. (See complete warranty policy for details.) © 2009 HID Global. All rights reserved. HID, the HID logo, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 06/2009 (RWKLB575 specific) Add 25 mA current for USB expansion modules and 20 mA for all others. (WKLB5/5 specific) Add 25 mA current for USB expansion modules and 20 mA for all others. Language support includes LCD text and quick start document. Field Enroller (Reader/Enroller) is field configurable into Reader/Enroller, Enroller-Only or Reader-Only reader types. Additionally, LCD language is field configurable. * Legary reader part numbers support simpler installation (no setup required) and C&D support. For maximum flexibility, select the field Erroller. ** One serial hardware interface only supported by RWKLB575 with expansion module. MKT-bioCLASS REVB DS-EN **ACCESS** experience. hidglobal.com

 Corporate

 North America

 15370 Barranca Pkwy

 Irvine, CA 92618

 U.S.A.

 Tel:
 1 800 237 7769

 Tel:
 1 949 732 2000

 Fax:
 +1 949 732 2360

Asia Pacific 19/F 625 King's Road North Point Island East Hong Kong Tel: +852 3160 9800 Fax: +852 3160 4809 Latin America Circunvalacion Ote. #201 B Despacho 2 Col. Jardines del Moral Leon 37160, Gto. Mexico Tel: +52 477 779 1492 Fax: +52 477 779 1493

Europe, Middle East & Africa Haverhill Business Park Phoenix Road Haverhill, Suffolk CB9 7AE England Tel: +44 (0) 1440 714 850 Fax: +44 (0) 1440 714 840

ASSA ABLOY