





---

---

**13.56 MHz Card Programming Information**

---

---

Format Number \_\_\_\_ (example: H10301) Bit Numbers \_\_\_\_ (example: 26 bit) Facility Code \_\_\_\_


Encoded Card # Start \_\_\_\_ Stop \_\_\_\_ Printed Card # Start \_\_\_\_ Stop \_\_\_\_

HID Elite ICE Number (if applicable) - \_\_\_\_ (Custom Format) Site Code \_\_\_\_ City Code \_\_\_\_ OEM Code \_\_\_\_

Special Instructions: \_\_\_\_

**For Contact Smart Chip selection, refer to Logical Access How to Order Guide. Standard configuration does not include a contact smart chip module.**

<sup>1</sup> For new artwork files, contact Customer Service for custom artwork number, lead-times, and cost.

<sup>2</sup> Cards ordered with plain white front and back packaging, with no HID artwork or with custom artwork, will still have a small HID logo  and reference number printed in the lower left-hand corner and a slot punch target printed on the back of the card.

<sup>3</sup> The Printed card number is placed in the bottom right-hand corner on the back of the card on Proximity Format Programming only.

<sup>4</sup> For Laser Engraved Printed numbers, consult factory for lead times and cost. When printed, by default the number is encoded MSB (most significant byte) -> LSB (least significant byte).

<sup>5</sup> Cards are provided with an optional slot punch at no additional charge. Some video imaging printers cannot accommodate pre-slot punched cards. Consult with the printer manufacturer prior to ordering.

<sup>6</sup> Includes a permanent Unique MIFARE 32 Bit Serial number. When printed the number is encoded MSB (most significant byte) -> LSB (least significant byte).

<sup>7</sup> Please note that cards shipped within North America are always laser-engraved. Inkjetted option is not available for these cards.

\* The composite construction is recommended for all cards with over-laminate applied.